SWISSMEX®

BACKPACK SPRAYER

Ideal for use in greenhouses, agriculture, landscaping, livestock farming, forestry and pest control.

- Ideal for use under the most demanding conditions thanks to the top quality materials and workmanship used to manufacture the sprayer.
- Multipurpose design makes this sprayer perfect for a variety of formula applications.
- Robust, high output pumping system requires less effort from the operator.
- High-quality materials that are corrosion resistant for long life.
- Large tank mouth with deep strainer that reduces the risk of spillage when filling.
- Tank lid with carrying handle and wand clips to make transportation and storage easy. One-way ventilation valve in tank lid prevents the operator from getting splashed by formula.
- Mechanical agitation keeps the formula mixed during spraying. It can be removed when not needed.
- Ergonomic pump handle folds upright for transportation and storage.
- Precision adjustable brass spray nozzle provides spray patterns from fine mist to jet stream.
- Double-braided fiber-reinforced vynil hose, is chemically resistant and flexible.
- Heavy-duty flow control with large filter for trouble-free spraying.
- Thick, wide, padded shoulder straps allow a fatigue-free spraying.
- Central attachement keeps the sprayer well-ballanced.
- Minimal maintenance required. Most service can be performed without tools.
- A wide assortment of accesorioes is available to enhance your spraying performance.





081195

4.7 gal 18 L



USED MAINLY FOR:

TECHNICAL CHARACTERISTICS



ACCESSORIES Brass spray lances (without spray tip, nut and gasket) FVR spray lances (without spray tip, nut and gasket) E219-136-C - 19.68"/50 cm =CÞ E219-142-C - 39.37"/1.0 m E219-143-C - 59.0"/1.50 m E219-195-C 10 E803-085 - 19.68"/50 cm with two nozzles, E803-400 - 15.74"/40 cm E219-146-C - 78.7"/2.0 m length 19.368" / 50 cm EXTENSION LANCE: Brass extensions (with connector) 2-nozzle brass extensions E219-500-C -26.3"/67 cm = E219-510-C - 39.37"/1.0 m Ū E219-520-C - 47.24"/1.20 m m E219-098-C - 15.74" / 40 cm 3-nozzle FVR extensions 3-nozzle brass extensions 2-nozzle FVR extensions _____ <u>_</u>₽= E219-140-C - 19.6"/50 cm E219-147-C - 39.37"/20 cm E219-138-C - 39.37"-de 1 m ind 219-420-C - 39.37-1.0 m E219-148-C - 28.7"/73 cm E219-151-C - 59.0 de 1.5 m COMPLETE NOZZLES SCREEN SHIELDS E219-099 -15.74" / 40 cm E219-117 - 8.6" / 22 cm E803-092-C E219-610-C E219-710-C

TECHNICAL DATA

ESPECIFICATIONS	DESCRIPTION
Tank capacity	4.7 gal/ 18L
Carrying Straps	Cushioned with belt
Pumping system	Internal piston with agitator
Hose	Fiber-vinyl – reinforced 3/8 inch (95.25mm)
Shut-off valve	Professional ergonomic with filter
Spray wand	Brass 20.5 inch /52 cm

Follow us:

SPECIFICATIONS	DESCRIPTION
Nozzle	Adjustable brass
Output per minute at 45 psi (3 bar)	21.3 fl oz (630 ml)
Working pressure	1-6 bar (15-87 psi)
Net weight	11.6 lbs / 5.3 kg
Weight with box	12.3 lbs / 5.6 kg
Dimensions	21.2x8.6x15.5" / 54x22x39.5 cm

Due to our commitment to technological progress, we reserve the right to make technical changes without prior notice.

Website: www.swissmex.com Email: exports@swissmex.com.mx Telephone: +52 (474) 74 122 16